(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 3 March 2005 (03.03.2005)

PCT

(10) International Publication Number WO 2005/019919 A1

(51) International Patent Classification7:

G02F 1/1347

(21) International Application Number:

PCT/IB2004/051455

- (22) International Filing Date: 13 August 2004 (13.08.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

PCT/IB03/03800

22 August 2003 (22.08.2003)

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): SHIBAZAKI, Minoru [JP/JP]; c/o Philips Japan Ltd., Philips Bldg., 2-13-37, Kohnan, Minato-ku, Tokyo 108-8507 (JP).
- (74) Agents: TSUGARU, Susumu et al.; c/o Philips Japan, Ltd., Philips Bldg., 2-13-37, Kohnan, Minato-ku, Tokyo 108-8507 (JP).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DISPLAY APPARATUS AND VIEWING ANGLE CONTROLLING UNIT



(57) Abstract: In the case that a voltage is not applied to a viewing angle controlling unit (11), a polarized plate (113) passes only the light vibrating in an arrow direction of the light entered into the viewing angle controlling unit (11). The light passed the polarized plate (113) passes through a liquid crystal layer (120) without twisting. The light passed the liquid crystal layer (120) also passes through a polarized plate (111). Therefore, the display becomes transparent (white) in any viewing angle (in all direction) in viewing angle non-controlling mode. In the case that a voltage is applied to a viewing angle controlling unit (11) by a first power source (13), a polarized plate (113) passes only the light vibrating in an arrow direction of the light entered into the viewing angle controlling unit (11). The light passed the polarized plate (113) passes through a liquid crystal layer (120) along liquid crystal molecules. The light passed the liquid crystal layer (120) also passes through a polarized plate (111). Therefore, the display becomes transparent in the center of the viewing angle controlling unit (11). The display becomes black in the side region of the viewing angle controlling unit (11) because of having a predetermined angle between an optical axis of the polarized plate (111) and an axis direction of the liquid crystal molecules. In viewing angle controlling mode, the display is visible when viewed from the front, while the display is invisible when viewed in a slanting direction.

